UNITEX LT90H / LT80H2 / LT70H2

Mac Windows Linux

World's Only USB Connection LTO High Speed USB 3.0/SAS LTO Tape Drive







- High speed data transfer at maximum 300MB/sec
- Plug and play with USB 3.0 interface
- Available also as a hybrid model with USB/SAS interface
- Large amounts of LTO capacity
- Support Mac, Windows, Linux

Features

- With USB plug and play connection, enable maintenance without stopping the server
- USB cable clamp prevents unexpected cable disconnection
- Support various use
- Backup & transfer large amounts of data
- Archive data in Broadcast/Video/Surveillance camera/Medical
- Countermeasure for Ransomware by managing data o -line
- LTFS3000 software is included
- Utility package is a GUI installation package which enables operation and management of all the LTFS functions on one window.
- No special knowledge and skills are required for data storage to LTO tape
- Enables move/copy of the data by drag-and-drop operation from Windows
- Explorer or MacOS X Finder to LTO tape drive by drag & drop
- Simultaneous operation of multiple drives



- LTFS enables share & exchange of data under multiple OS environment (Windows, MacOS, Linux)






USB: LT90H / LT80H2 / LT70H2



USB/SAS: LT90H



USB/SAS: LT80H2 / LT70H2



High Speed LT Series

Example of using LT series

Archive in Broadcast/Video industry



Archive at Factory/Production site



- Manage ever-increasing data assets easily with connecting to a laptop PC
- Pass and receive large amounts of data efficiently by LTO tape media
- Enable data sharing among different OS's with LTFS support



- Store CAD data such as drawings efficiently
- Ideal for long term storage of inspection data, inspection result, and trace data
- Record X-ray sensor data of foreign articles contamination and metal sensor data



Specification

High Speed USB3.0 LTO tape drive

0 1	•			
Model	LT90H USB	LT80H2 USB	LT70H2 USB	
Drive Type	LTO-9 Ultrium	LTO-8 Ultrium	LTO-7 Ultrium	
Interface	USB 3.0 (3.2 Gen1, Type B connector)			
Capacity	18.0TB (Native) / 45.0TB (2.5:1 Compression)	12.0TB (Native) / 30.0TB (2.5:1 Compression)	6.0TB (Native) / 12.0TB (2.5:1 Compression)	
Native data transfer (Max)	300MB/sec	300MB/sec	300MB/sec	
OS support	Mac / Windows / Linux			
Dimensions (mm)	213(W) x 370(D) x 58(H) mm			
Power Supply	AC100 - 240V ±10%, 50/60Hz			
Power Consumption	65VA			
Weight	4.5kg			
Operating Environment	Temperature: 10°C - 40°C, Humidity: 20% - 80% (No condensation)			
Kit Contents	LTO Tape Drive / USB3.0 cable / Power cable / LTO Cleaning Cartridge / User Guide (English) / LTFS3000 software (English)			

Hybrid USB 3.0/SAS LTO tape drive

Model	LT90H USB/SAS	LT80H2 USB/SAS	LT70H2 USB/SAS		
Drive Type	LTO-9 Ultrium	LTO-8 Ultrium	LTO-7 Ultrium		
Interface	USB 3.0 (3.2 Gen1, Type B connector) / SAS 6Gb miniSAS SFF8088 (LTO-8 + LTO-7) / SAS 12Gb miniSAS SFF8644 (LTO-9))				
Capacity	18.0TB (Native) / 45.0TB (2.5:1 Compression)	12.0TB (Native) / 30.0TB (2.5:1 Compression)	6.0TB (Native) / 15.0TB (2.5:1 Compression)		
Native data transfer (Max)	USB 3.0: 300 MB/sec. SAS 12Gb: 300 MB/sec.	USB 3.0: 300 MB/sek. SAS 6Gb: 300 MB/sek.	USB 3.0: 300 MB/sek. SAS 6Gb: 300 MB/sek.		
OS support	Mac / Windows / Linux				
Dimensions (mm)	213(W) x 370(D) x 58(H) mm				
Power Supply	AC100 - 240V ±10%, 50/60Hz				
Power Consumption	65VA				
Weight	4.5kg				
Operating Environment	Temperature: 10°C - 40°C, Humidity: 20% - 80% (No condensation)				
Kit Contents	LTO Tape Drive / USB3.0 cable / Power cable / LTO Cleaning Cartridge / User Guide (English) / LTFS3000 software (English)				



LTO is a trademark of HPE, IBM and Quantum. All other trademarks are the property of their respective owners. All information and specifications are subject to change without notice. Copyright © 2024 arkicon IT Sales-Channel Consulting. All rights reserved. Printed in Europe.

 ARKICON

 Eisenberger Str. 81 | 58708 Menden / Germany

 E-Mail: info@arkicon.de

 Phone: +49 157 582 55 199

www.arkicon.de