

# Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT3000IC

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

## Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	2700 W
Rated power in VA	3000 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
output connection type	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Number of rack unit	0U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	USB cable
Range of product	Smart-UPS


## Complementary

Communication port type	SmartConnect Ethernet port SmartSlot
Software package	SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>

Rates duty January 2016

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">RBC55</a> 
Battery charger power	271 W rated

## General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Colour	Black
Height	43.5 cm
Width	19.7 cm
Depth	54.4 cm
Product weight	52.5 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave

---

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

## Conformance

---

Product certifications	CE EAC RCM VDE UK PSTI
------------------------	------------------------------------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	------------------------------------------------------------------------------------

## Environmental

---

Acoustic level	53 dBA
----------------	--------

---

Heat dissipation	375 Btu/h
------------------	-----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Ambient air temperature for storage	-15...45 °C
-------------------------------------	-------------

---

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

---

Relative humidity	0...95 %
-------------------	----------

---

Storage Relative Humidity	0...95 %
---------------------------	----------

## Communications & Management

---

control panel	Multifunction LCD status and control console
---------------	----------------------------------------------

---

Emergency power off	Yes
---------------------	-----

---

Free slots	1
------------	---

---

Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
----------------------------	----------------------------------------------------------------------------------------------

---

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
-------	-----------------------------------------------------------------------------

## Surge Protection and Filtering

---

Surge energy rate	365 J
-------------------	-------

---

Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
-------------------	---------------------------------------------------------------------------------------------------------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	69.901 cm
------------------	-----------

---

Package 1 Width	38.100 cm
-----------------	-----------

---

Package 1 Length	76.200 cm
------------------	-----------

---

Package 1 Weight	63.548 kg
------------------	-----------

## Contractual warranty

---

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	------------------------------------------------------------------------------------------------------------------------------------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 3335

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

SCIP Number 0637234b-27c7-4e32-ae29-543dd4803a99

China RoHS Regulation [China RoHS declaration](#)

### Energy efficiency

Optimized Energy Efficiency Energy efficient product

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

Removable battery User replaceable

Take-back Yes